

HANDHELD HYDRAULIC



APP 13



APP 18

Power Packs

APT hydraulic power packs provide a cost-effective, portable solution to power the tools you need when you need to get to work right away. Two people can lift a hydraulic power pack into a vehicle for transport from site to site, making it a convenient alternative to towing a large compressor.

Features

- Power On Demand (APP 13 AND APP 18 TWIN ONLY) automatically idles the engine when tool is not in use to save fuel
- Foldable handle and wheels for transport on site
- Thermostatically controlled oil cooler for fast warm-up
- Variable flow on/off valve for simple tool change and slow startup

POWER PACKS	APP 13	APP 18	APP 18 TWIN
PART NUMBER	1807011038	1807016052	1807016054
Engine	13 HP Honda Gasoline	18 HP B&S Vanguard Gasoline	18 HP B&S Vanguard Gasoline
Weight Including Oil - lbs.	201	260	270
Dimensions L x W x H - in.	29 x 24 x 28	31 x 24 x 27	29 x 28 x 28
Oil Flow - gpm	5-8	5-10	2 x 5 or 1 x 5-8
Max. Pressure - psi	2,200	2,200	2,200
Fuel Capacity - gal.	1.8	1.9	1.9
Power on Demand (POD)	YES	NO	YES
Oil Control: Engine Oil	YES	YES	YES
Electric Start	NO	YES	YES
Sound Power Level Guaranteed, L _w (2000/14/EC) ¹ dB(A)	101	101	101
Sound Pressure Level, L _p , r=1m (ISO 11203) ¹ dB(A)	89	89	89
EHTMA Class	C/D	C/D/E	C/D/E

¹Two 4-liter bottles of biodegradable hydraulic oil are included in the delivery of each power pack. Hose is not included.



AWP 2



AWP 3

Water Pumps

Rugged APT hydraulic submersible pumps deliver excellent performance for their size and weight. They're also tough enough to stand up to small stones and debris. These models are designed for continuous operation in applications such as pumping water out of building sites, flooded excavations or cellars.

Features

- Cooled and lubricated by hydraulic oil
- Can be left to run dry without damage
- Handles small stones and debris up to 2.5 in. (AWP3)

WATER PUMPS	AWP 2	AWP 3	EXTRA HOSE	2-INCH	3-INCH
PART NUMBER	1806101785	1806101786	PART NUMBER	3378002100	3378002101
Weight - lbs.	24	29	Length - in.	33	33
Width - in.	9	12	Connection - in.	2	3
Oil Flow - gpm	5	8	Weight - lbs.	7	8
Working Pressure - psi	1,450	2,030	Description	Snap-lock quick-release coupling, female	Snap-lock quick-release coupling, female
Max. Pressure - psi	2,500	2,500	33-ft. discharge hose with snap-lite coupler included in pump delivery.		
Pump Head Max. - ft.	82	105			
Pump Flow Max. - gal./min.	222	507			
Discharge - in.	2	3			
Solids Handling Up To - in.	3/8	2-1/2			
HTMA Type	C	D			