



Forward Plate Compactors

APT forward soil plates are specially designed for compacting granular soils. They are ideal and most economical for small repair and maintenance work. Applications include asphalt, gravel, sand, and silt.

Features

- Specially shaped bottom plate
- Wheels for easy mobility
- Stowable handle
- Long-life V-belt
- FP 75: Removable 3.4-gal. water tank (FP 100: option)
- FP 75: Smart water distribution system
- Water tank is standard on FP 60A

MODEL	PLATE in.	ENGINE	POWER hp	FREQUENCY vpm	CENTRIFUGAL FORCE - ft.-lbs.	SOUND max dB(A)	H/A VIBRATION m/s ²	WEIGHT lbs.
FP 60A	14	HONDA	3.0	5,700	2,338	100	1.9	128
FP 75	17	HONDA	5.5	5,700	3,372	104	1.2	203
FP 100	20	HONDA	5.5	5,700	3,822	104	1.3	210



FP 60A



FP 100



FP 75

Rammers

High centrifugal force and speed contribute to deep and effective compaction. Applications include repair jobs, trenches, and foundations. The rammers feature a multi-functional fuel tank featuring a breather shut-off, electrical shut-off, fuel shut-off, and throttle control with three fixed positions (Stop/Idle/Run).

Features

- Sealed, multi-function tank with throttle control (Stop/Idle/Run)
- Honda 4-stroke engine
- Air breather system for easy start
- Easy access to all daily service points
- Efficient shock absorbers

MODEL	PLATE in.	ENGINE	POWER hp	FORCE/BLOW - lbs.-ft.	CENTRIFUGAL FORCE - ft.-lbs.	SOUND max dB(A)	H/A VIBRATION m/s ²	WEIGHT lbs.
TA 55	6-9	HONDA	3.0	2,985	2,985	104	6.4	133-136
TA 65	11	HONDA	3.0	3,330	3,330	104	4.9	152
TA 80	13	HATZ diesel	4.0	4,800	4,800	106	12.6	188



TA 55



TA 80



TA 65