

HANDHELD PNEUMATIC



Rock Drills

Features

Model 109 - 9 lb. class

- Clockwise rotation
- Stop-rotation feature
- Lightweight cast alum. handle
- Built-in automatic oiler

Model 115 - 15 lb. class

- Stop-rotation feature
- Counterclockwise rotation
- Built-in automatic oiler

Model 115 cont.

- Latch-type retainer
- Lightweight cast alum. handle

Model 137 - 30 lb. class

- 4 drilling speeds
- Replaceable piston stem bearing
- Available wet or dry
- Counterclockwise rotation

Model 137 cont.

- Rubber handle grips

Model 155 - 60 lb. class

- 3 drilling speeds
- Replaceable piston stem bearing
- Built-in automatic oiler
- Available wet or dry
- Counterclockwise rotation
- Rubber handle grips



Model	CHUCK SIZE in.	BORE in.	STROKE in.	BPM	CFM @90psi	WEIGHT lbs.	LENGTH in.	AIR INLET NPT
109	3/4 x 3-3/4 Round Slotted	1-1/4	1	3,400	19-21	9	15	3/8 female
115	7/8 x 3-1/4	1-15/16	1-3/8	2,900	32-36	19	18-3/8	3/8 male
137†	7/8 x 3-1/4 or 4-1/4 1 x 4-1/4	2-3/8	2-5/8	2,300	85-90	38	19-3/4	1/2 male
155	7/8 x 3-1/4 or 4-1/4 1 x 4-1/4	2-5/8	3	2,100	110-120	61	22-3/4	3/4 male

optional mufflers available for 109 & 155

†No built-in automatic oil reservoir - constant feed oiler recommended.

Clay/Trench Diggers

Features

- Deep case-hardened alloy steel cylinders
- Replaceable chuck bushing
- Latch-type retainer

Model 118 Clay Digger

- Patented ball valve design (U.S. pat. # 8,276,682 B2)
- Built-in automatic oiler
- D-style handle
- Inside trigger for better control and safety

Model 119 Trench Digger

- Patented ball valve design (U.S. pat. # 8,276,682 B2)
- Built-in automatic oiler
- T-style forged handle
- Rubber handle grips

Model 125 Clay Digger

- D-style handle
- Inside trigger for better control and safety
- Flapper valve design allows dirt to pass without stopping tool
- Replaceable chuck and piston stem bushing



MODEL	CHUCK in.	BORE in.	STROKE in.	BPM	CFM @90psi	WEIGHT lbs.	LENGTH in.	AIR INLET NPT
118	7/8 x 3-1/4 · 1 x 4-1/4	1-3/4	3-3/8	1,850	34-36	31	21-1/2	3/8 male
119	7/8 x 3-1/4 · 1 x 4-1/4	1-3/4	3-3/8	1,500	34-38	37	31	1/2 female
125	7/8 hex x 3-1/4	2-1/4	4-1/8	1,680	38-42	21	18-3/8	1/2 female

AMERICAN PNEUMATIC TOOLS

1000 S. Grand Ave.
Santa Ana, CA 92705

Tel 714.285.2828 | Fax 714.285.2829

Toll Free Tel 800.532.7402 | Fax 800.715.6502

BUILT TO LAST SINCE 1938

www.apr-tools.com

info@apr-tools.com

