



## APT Portable Compressors

With strong undercarriages and heavy-gauge bodies, APT portable compressors are robust and durable. Just pull one to the worksite and get busy.

### Features

- Extremely reliable Kubota diesel engines
- Ultra-efficient oil-injected air end
- All air outlets at rear of machine for ease of use
- Easy to service with great access to filters, engine and air receivers
- Trailer-mounted with road lights as standard
- Options include cold weather kits, aftercoolers, fine air filters, and more on select models

	APT 110 KD T4F	APT 185 T4F	APT 185 KDU T4	APT 440-100 JD T4F EB
Free Air Delivery - CFM	88	185	185	400-440
Working Pressure - psi (Bar)	100 (7)	58-100 (4-7)	100	150-100
Pressure Range - psi (Bar)	58-125 (4-8.6)	58-125 (4-8.6)	58-125 (4-8.6)	58-125 (4-8.6)
Discharge Outlets	2 @ 3/4"	2 @ 3/4"	1 x 1-1/2" NPT	1 @ 1-1/2" & 2 @ 3/4"
Oil Capacity - gal. (L)	1.45 (5.5)	2 (7.6)	2 (7.6)	5.4 (20.5)
Engine Make	Kubota	Kubota	Kubota	John Deere
Model	D 902 T4F	V2403	V2403-CR-E4B	4045HFC04
Displacement - L	1.123	2.4	2.4	4.5
Cylinders	3	4	4	4
EPA Tier	Tier 4 Final	Tier 4 Final	Tier 4 Final	Tier 4 Final
HP	24.8	49	49	115
Rated Speed (High) - rpm	3,000	2,700	2,700	2,400
Rated Speed (Low) - rpm	1,800	1,600	1,600	1,500
Fuel Tank Capacity - gal. (L)	8.5 (32)	20 (75)	20 (75)	52 (197)
Fuel Consumption @ 100% Load - gal./hr (L/hr)	1.11 (4.2)	2.3 (8.7)	2.7 (10.2)	6.5 (24.5)
Fuel Autonomy @ 100% Load - Hours	8	8	8	9
Sound Pressure Level @ 23' (7m) @ 75% Load - dB(A)	90	76	76	76
Trailer Dimensions (L x W x H) - in.	61 x 42 x 34	131 x 60 x 57	N/A	161 x 71.5 x 70
Weight (Wet) - lbs. (kg)	970 (440)	2,400 (1,089)	N/A	4,555 (2066)
Support Mounted (L x W x H) - in.	61 x 42 x 34	77 x 41 x 64	84 x 34 x 57	113 x 71.5 x 65
Weight (Wet) - lbs. (kg)	1,100 (499)	2,200 (1,000)	2,060 (935)	4,590 (2082)